

**CERTIFICATE**

No. A/11-176748 Rev 00
Date 2011-07-06 Page 1/2

INSPECTION CERTIFICATE acc to
EN 10 204 3.1

Processkontroll Items AB
Box 2088
444 02 STORA HÖGA
SWEDEN

INSPECTION STAMP
QA-TUBE

Customer References		Sandvik References	
710287	Customer order 2011-07-06	Order No. 252030	Subs No. 507092
003-00991 ITEMS		ABSMT No. 300-47314	Dispatch note 44247/54
		C.Code 15	

Material description	Steel/material Designations
SEAMLESS STAINLESS COLD FINISHED HYDRAULIC TUBING	Sandvik SS 3R60 2353 AISI AFNOR TP316/TP316L Z2CND17-13 W.nr DIN 1.4435 X 2 CRNIMO 18 14 3 EN no 1.4435
Steel making process Electric furnace	

Technical requirements
PED/23/EC, EN 10216-5 TC1 SS 219711, DIN 17458 TC1, NFA 49-117-09/85 ASTM A-213-09A AW, ASME SA-213-ED-10 AW, ASTM A-269-08 NACE MR0175/ISO 15156-3:2009, HRB Max 80

EXTENT OF DELIVERY								
It	Product designation	Heat	Lot	Pieces	Kg	M		
02	THT-3R60-14-2	047727	96166	10	36.0	60.00		
14.00 X 2.00								
				Total	10	36.0 60.00		
KEY TO HEAT		KEY TO LOT						
Heat Code	Heat No.	Lot Code	Lot No.					
047727	526750	96166	357346					
TEST RESULTS								
Chemical composition (weight%)								
Heat	C	Si	Mn	P	S	Cr	Ni	Mo
047727	0.016	0.40	1.78	0.031	0.008	17.36	13.13	2.53
N								
047727	0.034							
Chemical composition, product (weight%)								
Heat	C	Si	Mn	P	S	Cr	Ni	Mo
047727	0.020	0.38	1.75	0.028	0.008	17.34	13.09	2.52
N								
047727	0.031							
Quality assurance - Ulrik Rodling / QA-manager Tube & Pipe								
MTC Service / Certificates								

**CERTIFICATE****No. A/11-176748****Rev 00****Date 2011-07-06****Page 2/2****Tensile test at room temperature**

	Yield strength		Tensile strength	Elongation	
	MPa	MPa	MPa	%	%
Lot	Rp0.2	Rp1.0	Rm	A	2"
96166	249	283	556	64	64
	253	287	557	65	64

Hardness test

	Min	Max
Lot	HRB	HRB
96166	74	77

Following controls/tests have been satisfactorily performed:

- Flattening test.
- Flaring test
- PMI-test.
- Intergranular corrosion test acc to ASTM A-262 PR.E
- Intergranular corrosion test acc. to EN ISO3651-2, Method A.
- Leak test: Eddy current test acc to EN 10246-2, ASME SA-1016.
- Visual inspection and dimensional control.

Heat Treatment:

Solution annealed and quenched.

Marking:

SANDVIK 3R60 ASTM/ASME A/SA-213AW/A-269 NFA 49-117 EN 10216-5 TC1 SS 2353-22 W
NR 1.4435 TP 316/TP 316L Z2CND17-13 EN 1.4435 M S PK1 NDE 14.00 X 2.00 MM HT 5
26750 SC LOT 357346 DIN 2391/EN 10305-1 *QA-TUBE*

Approved acc. AD 2000-Merkblatt W0 and certified acc. to
Pressure Equipment Directive (97/23/EC) by
TUEV NORD; notified body, reg.no. 0045.

The number of tests are based on the size of the manufacturing lot
before cutting to finished lengths.

The delivered products comply with the specifications and
requirements of the order.

The material is manufactured according to a Quality system,
approved and registered to ISO 9001.

The certificate is produced with EDP and valid without signature.

TEST RESULTS TRANSFERRED FROM CERTIFICATE NO 00042360