

**CERTIFICATE**

A03/Z02

No. A/21-964278**Date**

2021-07-11

Rev**Page****00**

1/2

A02/Z03

INSPECTION CERTIFICATE acc to
EN 10204 3.1

A06

PROCESSKONTROLL ITEMS AB
BOX 2088
444 02 STORA HÖGA
SWEDEN

INSPECTION STAMP

QA-TUBE

Customer References A07 761328 Customer order 2021-06-24 003-00991 ITEMS -W		Sandvik References A08 Order No. Subs No. SMT Dispatch note 572454 699705 41793/54 SMT No. C.Code 300-33421 15																																																																																																					
Material description B01/B04 SEAMLESS STAINLESS COLD FINISHED HYDRAULIC TUBING Metallurgical process C70 Electric furnace		Steel/material Designations B02 Sandvik AISI 3R60 TP316/TP316L EN no 1.4435																																																																																																					
Technical requirements B03 ASTM A-213-19 AW, ASME SA-213-ED-19 AW, ASTM A-269-15A NACE MR0175/ISO 15156-3:-2015, NACE MR0103/ISO 17945-1:-2015 PED 2014/68/EU EN 10216-5 TC1 HRB MAX 80																																																																																																							
EXTENT OF DELIVERY B07-B13 <table><thead><tr><th>It</th><th>Product designation</th><th>Heat</th><th>Lot</th><th>Pieces</th><th>Kg</th><th>M</th></tr></thead><tbody><tr><td>02</td><td>THT-3R60-8-1.5</td><td>561784</td><td>37977</td><td>25</td><td>35.0</td><td>150.00</td></tr><tr><td></td><td>8.00 X 1.50</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td colspan="4" style="text-align: right;">Total</td><td>25</td><td>35.0</td><td>150.00</td></tr></tbody></table> TEST RESULTS Chemical composition (weight%) <table><thead><tr><th>Heat</th><th>C</th><th>Si</th><th>Mn</th><th>P</th><th>S</th><th>Cr</th><th>Ni</th><th>Mo</th></tr></thead><tbody><tr><td>561784</td><td>0.018</td><td>0.39</td><td>1.59</td><td>0.029</td><td>0.008</td><td>17.37</td><td>13.26</td><td>2.68</td></tr><tr><td></td><td>N</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>561784</td><td>0.036</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table> Chemical composition, product (weight%) <table><thead><tr><th>Heat</th><th>C</th><th>Si</th><th>Mn</th><th>P</th><th>S</th><th>Cr</th><th>Ni</th><th>Mo</th></tr></thead><tbody><tr><td>561784</td><td>0.018</td><td>0.39</td><td>1.61</td><td>0.029</td><td>0.005</td><td>17.39</td><td>13.19</td><td>2.68</td></tr><tr><td></td><td>N</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>561784</td><td>0.037</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>				It	Product designation	Heat	Lot	Pieces	Kg	M	02	THT-3R60-8-1.5	561784	37977	25	35.0	150.00		8.00 X 1.50						Total				25	35.0	150.00	Heat	C	Si	Mn	P	S	Cr	Ni	Mo	561784	0.018	0.39	1.59	0.029	0.008	17.37	13.26	2.68		N								561784	0.036								Heat	C	Si	Mn	P	S	Cr	Ni	Mo	561784	0.018	0.39	1.61	0.029	0.005	17.39	13.19	2.68		N								561784	0.037							
It	Product designation	Heat	Lot	Pieces	Kg	M																																																																																																	
02	THT-3R60-8-1.5	561784	37977	25	35.0	150.00																																																																																																	
	8.00 X 1.50																																																																																																						
Total				25	35.0	150.00																																																																																																	
Heat	C	Si	Mn	P	S	Cr	Ni	Mo																																																																																															
561784	0.018	0.39	1.59	0.029	0.008	17.37	13.26	2.68																																																																																															
	N																																																																																																						
561784	0.036																																																																																																						
Heat	C	Si	Mn	P	S	Cr	Ni	Mo																																																																																															
561784	0.018	0.39	1.61	0.029	0.005	17.39	13.19	2.68																																																																																															
	N																																																																																																						
561784	0.037																																																																																																						
Quality assurance - Sofia Åkesson / Q-Manager MTC Service / Certificates A05/Z02																																																																																																							

A01

AB SANDVIK MATERIALS TECHNOLOGY Reg No. 556234-6832 VAT No. SE556234683201
SE-81181 SANDVIKEN SWEDEN www.materials.sandvik mtc_service.smt@sandvik.com

**Tensile test at room temperature**

Lot	Yield strength		Tensile strength	Elongation	
	MPa	MPa	MPa	%	%
	Rp0.2	Rp1.0	Rm	A	4D
37977	278	314	568	51	51

Hardness test

Lot	Min	Max
	HRB	HRB
37977	70	71

Following controls/tests have been satisfactorily performed:

- Flattening test.
- Flaring test
- 100% PMI-test.
- Intergranular corrosion test acc to ASTM A-262 PR.E and EN ISO 3651-2A
- Leak test: Eddy current test acc to EN ISO 10893-1, ASME SA-1016.
- Visual inspection and dimensional control.

Heat Treatment:

Solution annealed at a temperature of Min 1040° C and quenched.

Marking:

SANDVIK 3R60 ASTM A213/A269 ASME SA213 COLD EN10216-5 TC1 AW EN 1.4435 TP316/3 16L CFA SML NDE 8.00 X 1.50 MM HT 561784 SS LOT 37977 MADE IN SWEDEN *QA-TUBE*

The raw material is free from radioactive contamination.

Material free from mercury contamination.

No welding or weld repair.

Approved acc. AD 2000-Merkblatt W0 and certified acc. to Pressure Equipment Directive (2014/68/EU, Annex 1 para 4.3) by TUEV NORD; notified body, reg.no. 0045.

The number of tests are based on the size of the manufacturing lot before cutting to finished lengths.

The delivered products comply with the specifications and requirements of the order.

The material is manufactured according to a Quality system, approved and registered to ISO 9001:2015.

No unauthorized alterations. The contents of this Inspection Certificate may not be modified or revised in any way without the prior written approval of Sandvik Materials Technology. Unauthorized alterations to the Inspection Certificate, including introduction of false, fictitious or fraudulent statements or entries, may be punishable by fines, imprisonment, or both. This Inspection Certificate may be copied only in the manner and for the purposes specified in Section 6 of EN 10204:2004. Contravention of this notice will be prosecuted to the fullest extent of applicable law.

The certificate is produced with EDP and valid without signature.

