

A02/Z03

INSPECTION CERTIFICATE acc to
EN 10204 3.1

A06

PROCESSKONTROLL ITEMS AB
BOX 2088
444 02 STORA HÖGA
SWEDEN

INSPECTION STAMP

QA-TUBE

Customer References A07 763602 Customer order 2023-02-02 003-00991 ITEMS -W	Alleima References A08 <table style="width: 100%;"> <tr> <td>Order No.</td> <td>Subs No.</td> <td>Dispatch note</td> </tr> <tr> <td>594982</td> <td>717740</td> <td>30256/54</td> </tr> <tr> <td>Suppl. No</td> <td>C.Code</td> <td></td> </tr> <tr> <td>300-51262</td> <td>29</td> <td></td> </tr> </table>	Order No.	Subs No.	Dispatch note	594982	717740	30256/54	Suppl. No	C.Code		300-51262	29																																																																					
Order No.	Subs No.	Dispatch note																																																																															
594982	717740	30256/54																																																																															
Suppl. No	C.Code																																																																																
300-51262	29																																																																																
Material description B01/B04 SEAMLESS STAINLESS COLD FINISHED INSTRUMENTATION TUBING Metallurgical process C70 Electric furnace	Steel/material Designations B02 <table style="width: 100%;"> <tr> <td>Alleima</td> <td>AISI</td> </tr> <tr> <td>3R60</td> <td>TP316/TP316L</td> </tr> <tr> <td>EN no</td> <td></td> </tr> <tr> <td>1.4435</td> <td></td> </tr> </table>	Alleima	AISI	3R60	TP316/TP316L	EN no		1.4435																																																																									
Alleima	AISI																																																																																
3R60	TP316/TP316L																																																																																
EN no																																																																																	
1.4435																																																																																	
Technical requirements B03 ASTM A-213-21B AW, ASME SA-213-ED-21 AW, ASTM A-269-15A NACE MR0175/ISO 15156-3:-2015, NACE MR0103/ISO 17945-1:-2015 PED 2014/68/EU EN 10216-5 TC1 HRB MAX 80																																																																																	
<table style="width: 100%;"> <tr> <td colspan="7">EXTENT OF DELIVERY</td> <td style="text-align: right;">B07-B13</td> </tr> <tr> <td style="text-align: center;">It</td> <td style="text-align: center;">Product designation</td> <td style="text-align: center;">Heat</td> <td style="text-align: center;">Lot</td> <td style="text-align: center;">Pieces</td> <td style="text-align: center;">Kg</td> <td style="text-align: center;">M</td> <td></td> </tr> <tr> <td style="text-align: center;">01</td> <td>THT-3R60-9.53-1.65 9.53 X 1.65 10786</td> <td style="text-align: center;">044458</td> <td style="text-align: center;">96663</td> <td style="text-align: center;">15</td> <td style="text-align: center;">29.0</td> <td style="text-align: center;">90.00</td> <td></td> </tr> <tr> <td colspan="4"></td> <td style="text-align: center;">Total</td> <td style="text-align: center;">15</td> <td style="text-align: center;">29.0</td> <td style="text-align: center;">90.00</td> </tr> </table> <table style="width: 100%;"> <tr> <td colspan="2">KEY TO HEAT</td> <td colspan="2">KEY TO LOT</td> </tr> <tr> <td style="text-align: center;">Heat Code</td> <td style="text-align: center;">Heat No.</td> <td style="text-align: center;">Lot Code</td> <td style="text-align: center;">Lot No.</td> </tr> <tr> <td style="text-align: center;">044458</td> <td style="text-align: center;">567046</td> <td style="text-align: center;">96663</td> <td style="text-align: center;">2083995-11</td> </tr> </table> TEST RESULTS Chemical composition (weight%) <table style="width: 100%;"> <tr> <td style="text-align: center;">Heat</td> <td style="text-align: center;">C</td> <td style="text-align: center;">Si</td> <td style="text-align: center;">Mn</td> <td style="text-align: center;">P</td> <td style="text-align: center;">S</td> <td style="text-align: center;">Cr</td> <td style="text-align: center;">Ni</td> <td style="text-align: center;">Mo</td> </tr> <tr> <td style="text-align: center;">044458</td> <td style="text-align: center;">0.021</td> <td style="text-align: center;">0.38</td> <td style="text-align: center;">1.54</td> <td style="text-align: center;">0.031</td> <td style="text-align: center;">0.009</td> <td style="text-align: center;">17.23</td> <td style="text-align: center;">13.12</td> <td style="text-align: center;">2.64</td> </tr> <tr> <td></td> <td style="text-align: center;">Co</td> <td style="text-align: center;">Ti</td> <td style="text-align: center;">Al</td> <td style="text-align: center;">N</td> <td colspan="4"></td> </tr> <tr> <td style="text-align: center;">044458</td> <td style="text-align: center;">0.13</td> <td style="text-align: center;"><0.003</td> <td style="text-align: center;">0.003</td> <td style="text-align: center;">0.036</td> <td colspan="4"></td> </tr> </table>		EXTENT OF DELIVERY							B07-B13	It	Product designation	Heat	Lot	Pieces	Kg	M		01	THT-3R60-9.53-1.65 9.53 X 1.65 10786	044458	96663	15	29.0	90.00						Total	15	29.0	90.00	KEY TO HEAT		KEY TO LOT		Heat Code	Heat No.	Lot Code	Lot No.	044458	567046	96663	2083995-11	Heat	C	Si	Mn	P	S	Cr	Ni	Mo	044458	0.021	0.38	1.54	0.031	0.009	17.23	13.12	2.64		Co	Ti	Al	N					044458	0.13	<0.003	0.003	0.036				
EXTENT OF DELIVERY							B07-B13																																																																										
It	Product designation	Heat	Lot	Pieces	Kg	M																																																																											
01	THT-3R60-9.53-1.65 9.53 X 1.65 10786	044458	96663	15	29.0	90.00																																																																											
				Total	15	29.0	90.00																																																																										
KEY TO HEAT		KEY TO LOT																																																																															
Heat Code	Heat No.	Lot Code	Lot No.																																																																														
044458	567046	96663	2083995-11																																																																														
Heat	C	Si	Mn	P	S	Cr	Ni	Mo																																																																									
044458	0.021	0.38	1.54	0.031	0.009	17.23	13.12	2.64																																																																									
	Co	Ti	Al	N																																																																													
044458	0.13	<0.003	0.003	0.036																																																																													
Quality assurance - Sofia Åkesson / Q-Manager MTC Service / Certificates		A05/Z02																																																																															



Chemical composition, product (weight%)

Heat	C	Si	Mn	P	S	Cr	Ni	Mo
044458	0.019	0.37	1.57	0.029	0.009	17.27	13.00	2.60
	N							
044458	0.032							

Tensile test at room temperature

Lot	Yield strength		Tensile strength	Elongation	
	MPa	MPa	MPa	%	%
	Rp0.2	Rp1.0	Rm	A	2"
96663	277	307	560	69	63

Hardness test

Lot	Min	Max
	HRB	HRB
96663	76	77

Following controls/tests have been satisfactorily performed:

- Flattening test.
- Flaring test
- 100% PMI-test.
- Intergranular corrosion test acc to ASTM A-262 PR.E and EN ISO 3651-2A
- Leak test: Eddy current test acc to EN ISO 10893-1, ASME SA-1016.
- Visual inspection and dimensional control.

Heat Treatment:

Solution annealed at a temperature of Min 1040° C and quenched.

Marking:

3R60 ASTM/ASME A/SA213 A269 COLD EN 10216-5 TC1 AW TP 316/TP 316L EN 1.4435 CF A SML NDE 9.53 X 1.65 MM 3/8" X 16 BWG/SWG HT 567046 SZ LOT 2083995-11 MADE B Y ALLEIMA IN CZECHIA *QA-TUBE*

The raw material is free from radioactive contamination.

Material free from mercury contamination.

No welding or weld repair.

Approved acc. AD 2000-Merkblatt W0 and certified acc. to Pressure Equipment Directive (2014/68/EU, Annex 1 para 4.3) by TUEV NORD; notified body, reg.no. 0045.

The number of tests are based on the size of the manufacturing lot before cutting to finished lengths.

The delivered products comply with the specifications and requirements of the order.

The material is manufactured according to a Quality system, approved and registered to ISO 9001:2015.



No unauthorized alterations. The contents of this Inspection Certificate may not be modified or revised in any way without the prior written approval of Alleima.

Unauthorized alterations to the Inspection Certificate, including introduction of false, fictitious or fraudulent statements or entries, may be punishable by fines, imprisonment, or both. This Inspection Certificate may be copied only in the manner and for the purposes specified in Section 6 of EN 10204:2004. Contravention of this notice will be prosecuted to the fullest extent of applicable law.

The certificate is produced with EDP and valid without signature.

Alleima, formerly Sandvik Materials Technology. During a brand transition period, both Sandvik and Alleima marking on products may exist.

TEST RESULTS TRANSFERRED FROM CERTIFICATE NO C-8341/30

